






1056 Driftwood



138 Ivory Oak



150 Cinnamon Walnut




154 Almond Oak




2013 White Sand



2014 Marina



203 Tawny Oak




507 Wheat Oak




5091 Lighthouse




7089 Wild Dunes




5092 Sea Glass




556 Smoky Oak



562 Neutral Oak




592 Shadow Oak




698 Auburn Oak



7089 Wild Dunes




728 Jade Oak



734 Umber Oak



762 Hazel Oak



820 Amber Oak

Genuine (G) WW543

	US Units	Metric Units
Style Number	WW543	
Construction	SPC	
Profile	Click	
Size	7" x 48"	17.78 cm x 121.92 cm
Overall Thickness	0.189"	4.8 mm
Wear Layer Thickness	12 mil (0.012")	0.3 mm
Finish	ArmourBead	
Edge Description	Micro Bevel	
Area per Carton	18.68 sq ft	1.74 sq m
Area per Pallet	1494.4 sq ft	138.83 sq m
Installation	Floating	
Installation Grade	Above, On, Below	
Ortho-Phthalates Free	Yes	
FloorScore Certified	Yes	
Residential Warranty	30 Years	
Commercial Warranty	7 Year Light Commercial	
Smoke Density (ASTM E662, Flaming Mode)	Passes, <450	
Radiant Panel (ASTM E648)	Passes, Class I	

Suggested Adhesive

Style Name	Style Number
Shaw T-180 (4 gal)	101LV

Coordinating Trim



Style Number	Baby Threshold*	T-Molding*	Multi-Purpose Reducer*	Quarter Round	Overlap Stairnose*	Flush Stairnose
0736V	VSBT2	VSTMD	VSMRP	VSQTR	VSSTN	VFSN2
Length	94"	72"	72"	94"	94"	94"

*Packaged with molding track

TREADZ®



Center	LVCTR
Right	LVCAR
Left	LVCAL
White Riser	LVWRI*

*packages of 3

SOFT SILENCE
ACOUSTICAL PAD